DECLARATION OF PERFORMANCE

DavosALow-CPR-2020/08/04-GB



PRODUCT

Product typeFireplace with steel insertType designationDavos A Low with N-29A

Product identificationSee serial number plate on productIntended area of useHeating of rooms in residential buildings

Fuel Wood

MANUFACTURER

Name Nordpeis AS

Address Gjellebekkstubben 11 3420 Lierskogen, Norway

CHECKS

According to AVCP System 3

Standard EN 13240:2001 /A2:2004 / AC:2007

Test institute Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625

has checked declared performance and issued test report no. RRF- NS 20 5571, RRF- 29 19 5299,

RRF- 40 20 5447

DECLARED PERFORMANCE

Essential Characteristic	Performance			Harmonized technical specification
Reaction to fire	A1			
Minimum distances to combustible material	0	mm rear		
	0/210	mm side		
	other safety distances			
	according product manual			
Risk of falling embers	Approved			
Emission from combustion:]
Carbon monoxide at 13% O ₂	CO =	1000	mg/m^3	
Nitrogen oxides at 13% O ₂	NOx =	107	mg/m^3	EN 13240:2001 /
Organic gaseous compounds at 13% O ₂	OGC =	64	mg/m^3	A2:2004 / AC:2007
Particulate matter at 13% O ₂	PM =	26	mg/m^3	,
Surface temperatures	Approved			
Cleanability	Approved			
Mechanical durability	Approved			_
Releases of Hazardous Substances	Approved]
Nominal output	P =	8,9	kW]
Flue gas temperature	t _a =	269	°C]
Energy efficiency	η=	82,0	%	

The udersigned is responsible for the manufacture and conformity with declared performance

Stian Varre, CEO Nordpeis AS Lierskogen, 28.05.2024