DECLARATION OF PERFORMANCE

DavosPLow-CPR-2020/07/08-GB



PRODUCT

Product typeFireplace with steel insertType designationDavos P Low with N-29P

Product identificationSee serial number plate on productIntended area of useHeating of rooms in residential buildings

Fuel Wood

MANUFACTURER

Name Nordpeis AS

Address Gjellebekkstubben 11 3420 Lierskogen, Norway

CHECKS

According to AVCP System 3

Standard EN 13240:2001 /A2:2004 / AC:2007

Test institute Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625

has checked declared performance and issued test report no.RRF- 29 19 5396, RRF- 40 20 5504

DECLARED PERFORMANCE

Essential Characteristic	Performance			Harmonized technical specification
Reaction to fire	A1			
Minimum distances to combustible material	0	mm rear		
	1000	mm side		
	other safe	ty distances		
	according product manual			
Risk of falling embers	Approved]
Emission from combustion:				
Carbon monoxide at 13% O ₂	CO =	875	mg/m^3	
Nitrogen oxides at 13% O ₂	NOx =	108	mg/m^3	EN 13240:2001 /
Organic gaseous compounds at 13% O ₂	OGC =	70	mg/m^3	A2:2004 / AC:2007
Particulate matter at 13% O ₂	PM =	28	mg/m³	
Surface temperatures	Approved Approved Approved			
Cleanability				
Mechanical durability				
Releases of Hazardous Substances				
Nominal output	P =	10,5	kW	
Flue gas temperature	t _a =	286	°C	
Energy efficiency	η=	78,0	%	

The udersigned is responsible for the manufacture and conformity with declared performance

Stian Varre, CEO Nordpeis AS