DECLARATION OF PERFORMANCE

Q34AL-CPR-2013/12/02-GB



PRODUCT

Product typeSheet Steel InsertType designationQ-34 AL R/L

Product identificationSee serial number plate on productIntended area of useHeating of rooms in residential buildings

Fuel Wood

MANUFACTURER

Name Nordpeis AS

Address Gjellebekkstubben 11 3420 Lierskogen, Norway

CHECKS

According to AVCP System 3

StandardEN 13229:2001 / A2:2004 / AC:2006 / AC:2007Test instituteRein-Ruhr Feuerstatätten Prüfstelle, NB 1625Danish Technological Institute, NB 1235

has checked declared performance and issued test report no. RRF- 29 13 3454, ELAB 2023-MUR,

RRF- 29 21 6042

DECLARED PERFORMANCE

Essential Characteristic	Performance			Harmonized technical specification
Reaction to fire	A1			
Minimum distances to non-combustible material	15 mm rear]
	15	mm side		
	other safety distances			
	according		anual	
Risk of falling embers	Approved]
Emission from combustion:				
Carbon monoxide at 13% O ₂	CO =	875	mg/m^3	
Nitrogen oxides at 13% O ₂	NOx =	91	mg/m^3	EN 13229:2001 /
Organic gaseous compounds at 13% O ₂	OGC =	59	mg/m^3	A2:2004 / AC:2006 /
Particulate matter at 13% O ₂	PM =	17	mg/m³	AC:2007
Surface temperatures	Approved			
Cleanability	Approved			
Mechanical durability	Approved			
Releases of Hazardous Substances	Approved			
Nominal output	P =	7,0	kW	
Flue gas temperature at nominal output	t _a =	273	°C	
Energy efficiency	η=	81,0	%	

The udersigned is responsible for the manufacture and conformity with declared performance

Stian Varre, CEO Nordpeis AS Lierskogen, 10.06.2024