## **DECLARATION OF PERFORMANCE**

N-21A-CPR-2023/05/08-GB



**PRODUCT** 

Product type Sheet Steel Insert
Type designation N-21A Exclusive

Product identificationSee serial number plate on productIntended area of useHeating of rooms in residential buildings

**Fuel** Wood

**MANUFACTURER** 

Name Nordpeis AS

Address Gjellebekkstubben 11 3420 Lierskogen, Norway

**CHECKS** 

According to AVCP System 3

**Standard** EN 13229:2001/A2:2004/AC:2007

**Test institute** Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625

has checked declared performance and issued

test report no. RRF - 29 22 6295

## **DECLARED PERFORMANCE**

Essential Characteristic		Performa	Harmonized technical specification	
Reaction to fire	A1			
Minimum distances to non-combustible material	15	mm rear		
	400	mm side		
	other safety distances			
	according product manual			
Risk of falling embers	Approved			
Emission from combustion:				
Carbon monoxide at 13% O <sub>2</sub>	CO =	1125	$mg/m^3$	
Nitrogen oxides at 13% O <sub>2</sub>	NOx =	106	$mg/m^3$	EN 13229:2001 /
Organic gaseous compounds at 13% O <sub>2</sub>	OGC =	92	$mg/m^3$	A2:2004 /AC:2007
Particulate matter at 13% O <sub>2</sub>	PM =	14	mg/m³	
Surface temperatures	Approved			
Cleanability	Approved			
Mechanical durability	Approved			
Releases of Hazardous Substances	Approved			
Nominal output	P =	5,4	kW	
Flue gas temperature	t <sub>a</sub> =	228	°C	
Energy efficiency	η=	82,0	%	

The udersigned is responsible for the manufacture and conformity with declared performance

Stian Varre, CEO Nordpeis AS Lierskogen, 12.06.2024