## **DECLARATION OF PERFORMANCE**

SalzL-CPR-2018/06/26-GB



**PRODUCT** 

Product typeSlow heat release applianceType designationSalzburg L ; Salzburg L+1Product identificationSee product instruction manual

Intended area of use Heating of rooms in residential buildings

**Fuel** Wood

**MANUFACTURER** 

Name Nordpeis AS

Address Gjellebekkstubben 11 3420 Lierskogen, Norway

**CHECKS** 

According to AVCPSystem 3StandardEN 15250:2007

**Test institute** Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625

has checked declared performance and issued

test report no. RRF - 50 16 4448-1

## **DECLARED PERFORMANCE**

Essential Characteristic	Performance			Harmonized technical specification
Reaction to fire	A1			
Minimum distances to combustible material	50	mm rear		
	300	mm side		
	other safety distances			
	according product manual			
Risk of falling embers	Approved			
Emission from combustion:				
Carbon monoxide at 13% O <sub>2</sub>	CO =	875	mg/m <sup>3</sup>	
Nitrogen oxides at 13% O <sub>2</sub>	NOx =	118	mg/m <sup>3</sup>	
Organic gaseous compounds at 13% O <sub>2</sub>	OGC =	75	mg/m <sup>3</sup>	
Particulate matter at 13% O <sub>2</sub>	PM =	23	mg/m <sup>3</sup>	EN 15250:2007
Surface temperatures	Approved			
Cleanability	Approved			
Mechanical durablity	Approved			
Releases of Hazardous Substances	Approved			
Total thermal output		45,14	kWh	
Nominal output after elapsed time at 25% of max. mean temperature	P =	2,0	kW	
Flue gas temperature at nominal output	t <sub>a</sub> =	113	°C	
Energy efficiency	η=	90	%	

The udersigned is responsible for the manufacture and conformity with declared performance

Stian Varre, CEO Nordpeis AS Lierskogen, 05.06.2024