## **DECLARATION OF PERFORMANCE**

SalzMII-CPR-2020/06/08-GB



**PRODUCT** 

**Product type** Slow heat release appliance

Type designation Salzburg M II

**Product identification** See product instruction manual

Intended area of use Heating of rooms in residential buildings

**Fuel** Wood

**MANUFACTURER** 

Name Nordpeis AS

Address Gjellebekkstubben 11

3420 Lierskogen, Norway

**CHECKS** 

According to AVCP System 3
Standard EN 15250:2007

**Test institute** Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625

has checked declared performance and issued test report no. RRF - 50 20 5549, RRF - 50 11 2758

## **DECLARED PERFORMANCE**

				Harmonized
Essential Characteristic	Performance			technical
				specification
Reaction to fire	A1			
Minimum distances to combustible material	50/150	mm rear		
	100	mm side		
	other safe	ty distances		
	according product manual			
Risk of falling embers	Approved			
Emission from combustion:				
Carbon monoxide at 13% O <sub>2</sub>	CO =	1188	$mg/m^3$	
Oxygen nitride NOx at 13% O <sub>2</sub>	NOx =	142	$mg/m^3$	
Organic Gaseous Carbon at 13% O <sub>2</sub>	OGC =	81	$mg/m^3$	
Particulate Matter at 13 O <sub>2</sub>	PM =	32	mg / m <sup>3</sup>	EN 15250:2007
Surface temperatures	Approved			
Cleanability	Approved			
Mechanical durablity	Approved			
Releases of Hazardous Substances	Approved			
Total thermal output		39,4	kWh	
Nominal output after elapsed time at 25% of max. mean				
temp.	P =	2,4	kW	
Flue gas temperature at nominal output	t <sub>a</sub> =	157	°C	
Energy efficiency	η=	84	%	

 $The\ uder signed\ is\ responsible\ for\ the\ manufacture\ and\ conformity\ with\ declared\ performance$ 

Stian Varre, CEO Nordpeis AS Lierskogen, 05.06.2024